



MonierLifetile
A Boral Roofing Company

Zephyr Block™

- Moldable weather block
- Blocks entry of wind driven moisture between field and trim tiles
- Rollable installation saves time and reduces labor costs
- Adhesion and flexible to work with all tile profiles
- Available in 2 width sizes
- UV resistant



Zephyr Block™ is the choice for all non vented weather blocking needs. Manufactured for durability and flexibility, it will reduce installation labor and costs while increasing the longevity of the entire roof. The material composition Polyisobutylene (PIB) between folded aluminum composite foil and Butyl adhesive strips provides for the moldability to make this a truly universal weather blocking solution to seal all roof abutments and for all tile profiles.

The installation recommendations are being furnished as general information guidelines. However, installation is the responsibility of the roofing contractor and must be performed in accordance with prevailing building code requirements.

ZEPHYRBlock™
Roof System COMPONENTS

Installation Recommendations



Step 1:
Unroll Zephyr Block evenly over the ridge board.



Step 2:
Peel off butyl strip.



Step 3:
Form the adhesive to the surface of the ridge tiles. Ensure that the outer edges of the Zephyr Block are fully covered by the ridge tiles. Shape the Zephyr Block according to the profile of the tile start by pressing down from the peak to the valley.

Note: surface of the ridge tiles must be clean and dry to ensure proper seal



Step 4:
Attach trim tiles with one 2" screw.

Features & Benefits

Weather Block

- High quality adhesive enables a weather tight seal
- Uniquely flexible to conform to work with all tile profiles
- Blocks entry of wind driven moisture between field and trim tile

Ease of Application

- Easy roll out on all ridge and hip areas
- Lightweight and easy to carry on the roof

Cost Effective

- Rollable installation reduces labor and total installation costs
- Use a common 2"x 2" nailer (MLT QuickDrive® Screw Gun and Case) on all profiles reduces lumber costs and eliminates the need to inventory multiple ridge board sizes

Ordering Information

Part Numbers

91078 - 11" width x 33' length 280mm - Profiles - Low and Medium

91079 - 13.5" width x 33' length 340mm - Profile - High

Packaging

11"- 4 rolls per box weight 5.95 lbs per roll - 24.03 lbs per box - 144 rolls per pallet

13.5"- 4 rolls per box weight 7.28 lbs per box - 120 rolls per pallet

SALES OFFICES NATIONWIDE

PHOENIX • ARIZONA
GILROY • CALIFORNIA
LATHROP • CALIFORNIA
RIALTO • CALIFORNIA
STOCKTON • CALIFORNIA

DENVER • COLORADO
POMPANO BEACH • FLORIDA
LAKE WALES • FLORIDA
ATLANTA • GEORGIA
KAPOLEI • HAWAII

KANSAS CITY • MISSOURI
HENDERSON • NEVADA
KATY • TEXAS
TACOMA • WASHINGTON

1-800-571-TILE (8453)
www.boralna.com

