



Material Safety Data Sheet

SECTION I - PRODUCT AND COMPANY IDENTIFICATION	
Identity (As used on Label and List) Boral Roofing Rapid Flashing	Trade Names Wakaflex
Manufacturer's Name Boral Roofing	Emergency Telephone Number (800) 274-6505 ext. 1452
Address (Number, Street, City, State, and ZIP Code) Boral Roofing 7575 Irvine Center Drive, Suite 100 Irvine, CA 92618 - 2930	Telephone Number for Information (949) 756-1605 ext. 1434 Date Prepared June 2008

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION			
Hazardous Components/CAS Number	OSHA PEL (mg/m ³)	ACGIH TLV (mg/m ³)	% by Weight
N/A – Article under OSHA definition			

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS	
Boiling Point Not applicable	Specific Gravity (H ₂ O = 1) Lighter than water
Vapor Pressure (mm Hg.) Not applicable	Melting Point 212°F (100°C)
Vapor Density (AIR = 1) Not applicable	Evaporation Rate (Butyl Acetate = 1) Not applicable
Solubility in Water Negligible	
Appearance and Odor No odor. Long thin sheets in Anthracite / Red / Brown / Light Grey with aluminum mesh and adhesive edges	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA			
Flash Point (Method Used) 392F (200C) Ignition Point	Explosive Limits Not applicable	LEL	UEL
Extinguishing Media ABC Fire Extinguisher/water/foam			
Special Fire Fighting Procedures None			
Unusual Fire and Explosion Hazards None			

SECTION V - REACTIVITY DATA			
Stability	Unstable		Conditions to Avoid
	Stable	3	None
Incompatibility (Materials to Avoid) None			
Hazardous Decomposition or Byproducts None			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	3	None

SECTION VI - HEALTH HAZARD DATA

Health Hazards (Acute and Chronic)

None Known

SECTION VII - FIRST AID AND EMERGENCY PROCEDURES

N/A

SECTION VIII - PERSONAL PROTECTION AND CONTROL MEASURES

None required

SECTION IX - HANDLING AND STORAGE INFORMATION

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Not applicable.

WASTE DISPOSAL METHOD: Scrap is classified as a (non-RCRA hazardous) solid waste for disposal.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: None for normal handling and storage. Ideal storage between 5C (41F) to 25C (77F). Above 100C (212F), potential for butyl softening and difficulties to release protective foil for application.

SECTION X - OTHER REGULATORY INFORMATION

CLASSIFICATION OF PRODUCT FOR REGULATORY PURPOSES: This is an "article" as defined in 29 CFR § 1910.1200(b)(6)(V) and 40 CFR §372.38. As an article, an MSDS is not required for the product's normal storage, transportation and use.

COMMUNITY RIGHT TO KNOW: Emergency Planning and Community-Right-To-Know Act (EPCRA) §311/312 Categorizations for hazardous substance inventory [40 CFR §370]. This product is an exempt article. EPCRA §313 Toxic Chemical Release Inventory (TRI) Reporting [40 CFR §372]. This product in normal construction use is an exempt article.

TRANSPORTATION:

DOT Hazard Classification: Not Regulated [49 CFR §171 *et seq.*]

UN/NA Code: None

Placard Required: None

Labeling Requirement: None

RESOURCE CONSERVATION AND RECOVERY ACT (RCRA): As supplied does not meet any of the RCRA characteristics of hazardous waste (ignitable, corrosive, reactive, or toxic), nor are they listed hazardous wastes [40 CFR §261]. State and local requirements for disposal as non-hazardous solid waste should be determined.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON THE DATA REASONABLY BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN. THE PREPARER ACCEPTS NO RESPONSIBILITY AND DISCLAIMS ALL LIABILITY FOR ANY HARMFUL HEALTH EFFECTS WHICH MAY BE CAUSED BY EXPOSURE TO AIRBORNE DUST PARTICLES CREATED BY DRY SAWING, GRINDING, OR DRILLING OF ROOF TILES, NOR ANY OTHER INJURY RESULTING FROM THEIR USE. CUSTOMERS/USERS OF THIS PRODUCT MUST COMPLY WITH ALL APPLICABLE HEALTH AND SAFETY LAWS, REGULATIONS, AND ORDERS.